


底座用固定座 ◀ 标准型/引导型




代码	类型	材质		表面处理
		国标	相当	
OBW01	标准型	Q235	SS400	发黑
OBW02				无电解镀锌
OBW06		OCr18Ni9	SUS304	/
OBW11	引导型	Q235	SS400	发黑
OBW12				无电解镀锌

■如防锈有要求，请优先选用不锈钢材质或无电解镀锌产品。


D=6~13




D=15~30



标准型
OBW01/02/06



引导型
OBW11/12



型号			D2	B	H	D1	T	E	d1	d2	h	F	W	b	Ph7	S	支持安装螺钉
代码	Dh7																
标准型 OBW01 OBW02 OBW06 引导型 OBW11 OBW12	6	+0.012 0	28	12	16	12	5	9	3.5	6.5	4	20	-	3.5	12	5	M3
	8	+0.015 0	32	15	22	15		12	4.5	8	5	24		4.5	15		M4
	10	0	38	18	26	18		15	5.5	9.5	6	30		18	M5		
	12	+0.018 0	42	20	32	20	8	18	6.6	11	7	32	5.5	20	M6		
	13		48	32	40	25		10	23	9	14			10	25		M8
	15		0	48	32	40	25		15	31	11	18	12	35	25		6.6
	16	+0.021 0	75	38	50	30	38	14		20	15	45	35	9	38		M12
	20		80	55	75	45	45	18		26	19	50	40		45		M16



请按图示订货

■ OBW12-D6

型号		D2
代码	Dh7	
OBW12	6	28



交期Delivery

5天

发货

○本产品发货时间不含周日

