


圆线螺旋弹簧 ◀ 外径基准型(弹簧钢)



代码	类型	材质		允许位移量	弹簧常数公差	表面处理
		国标	相当			
AWY	外径基准型	琴钢丝	SWP	$L \times 75\%$	$\pm 10\%$	发黑



■ 外径D公差: $\varnothing 10$ 以下-0.5mm~0mm
 $\varnothing 13$ 以上-0.8mm~0mm
 ■ 长度L公差: 50以下 ± 1.5 , 55以上 ± 2.5
 压紧长度为参考值, 因批次不同会有偏差。
 理论使用次数100万次
 两端均未进行磨削加工。

代码	型号		d	压紧长度	Fmax	N (kgf) max	
	D	L					
AWY	3	5	0.16	1	3.75	0.38	
		10	0.2	2	7.5	0.75	
		15	0.23	3.6	11.2	1.12	
		20	0.23	3.6	15	1.5	
		25	0.25	5.5	18.7	1.87	
	4	30	0.26	6.5	22.5	2.25	
		5	0.2	1.1	3.75	0.38	
		10	0.23	1.9	7.5	0.7	
		15	0.23	1.9	11.2	1.1	
		20	0.25	2.7	15	1.5	
		25	0.29	5	18.7	1.8	
		30	0.29	5	22.5	2.2	
		35	0.32	7.7	26.2	2.6	
		40	0.32	7.7	30	2.9	
		5	10	0.25	1.7	7.5	0.7
	15		0.25	1.7	11.2	1.1	
	20		0.3	3.2	15	1.5	
	25		0.3	3.2	18.7	1.8	
	30		0.35	6.3	22.5	2.2	
	35		0.35	6.3	26.2	2.6	
	40		0.38	9.2	30	2.9	
	45		0.38	9.2	33.7	3.3	
	50		0.38	9.2	37.5	3.7	
	6		10	0.3	2.1	7.5	0.75
		15	0.32	2.8	11.2	1.1	
		20	0.32	2.8	15	1.5	
		25	0.35	4.1	18.7	1.8	
		30	0.38	5.6	22.5	2.2	
		35	0.38	5.6	26.2	2.6	
		40	0.4	7.2	30	2.9	
		45	0.4	7.2	33.7	3.3	
		50	0.4	7.2	37.5	3.7	
		55	0.45	12.2	41.2	4	
		60	0.45	12.2	45	4.4	
		65	0.45	12.2	48.7	4.8	
		70	0.45	12.2	52.5	5.1	
		8	10	0.35	2.1	7.5	0.75
			15	0.38	3	11.2	1.1
	20		0.4	3.5	15	1.5	
	25		0.4	3.5	18.7	1.8	
30	0.45		5.7	22.5	2.2		
35	0.45		5.7	26.2	2.6		
40	0.45		5.7	30	2.9		

代码	型号		d	压紧长度	Fmax	N (kgf) max	
	D	L					
AWY	8	45	0.45	5.7	33.7	3.3	
		50	0.5	9	37.5	3.7	
		55	0.5	9	41.2	4	
		60	0.5	9	45	4.4	
		65	0.5	9	48.7	4.8	
		70	0.5	9	52.5	5.1	
		10	15	0.5	3	11.2	2.26
			20	0.55	4.6	15	2.9
			25	0.55	4.6	18.7	3.7
			30	0.6	6.6	22.5	4.4
	35		0.6	6.6	26.2	5.1	
	40		0.65	9.1	30	5.9	
	45		0.65	9.1	33.7	6.6	
	50		0.65	9.1	37.5	7.4	
	55		0.7	12.6	41.2	8.1	
	60		0.7	12.6	45	8.8	
	13	65	0.7	12.6	48.7	9.6	
		70	0.7	12.6	52.5	10.3	
		20	0.6	3.9	15	2.9	
		25	0.65	5.1	18.7	3.7	
		30	0.65	5.1	22.5	4.4	
		35	0.7	6.7	26.2	5.1	
		40	0.75	8.7	30	5.9	
		45	0.75	8.7	33.7	6.6	
		50	0.8	11.6	37.5	7.4	
		55	0.8	11.6	41.2	8.1	
	16	60	0.8	11.6	45	8.8	
		65	0.85	15.3	48.7	9.6	
		70	0.85	15.3	52.5	10.3	
		20	0.65	3.6	15	2.9	
		25	0.7	4.6	18.7	3.7	
		30	0.75	5.7	22.5	4.4	
		35	0.8	7	26.2	5.1	
		40	0.85	9	30	5.9	
		45	0.85	9	33.7	6.6	
		50	0.9	11.3	37.5	7.4	

■ AWY: Fmax(容许位移量) = $L \times 75\%$



请按图示订货

■ AWY-D3-L10

型号

代码	D	L
AWY	3	5 10



交期Delivery

4天 发货

○ 本产品发货时间不含周日