


免键梯形齿同步带轮 ◀ H型(齿距12.7)



型号				材质			表面处理		
皮带宽度 19.1mm (3/4inch)	皮带宽度 25.4mm (1inch)	皮带宽度 38.1mm (1.5inch)	皮带宽度 50.8mm (2inch)	带轮	法兰	衬套	带轮	法兰	衬套
A : 21 W : 26	A : 27 W : 32	A : 40 W : 45	A : 54 W : 59	铝合金	铝合金	S45C	本色阳极氧化		发黑
VAC01□□H075	VAC11□□H100	VAC21□□H150	VAC31□□H200				发黑	发黑	发黑
VAC03□□H075	VAC13□□H100	VAC23□□H150	VAC33□□H200	S45C	SPCC		无电解镀锌		
VAC04□□H075	VAC14□□H100	VAC24□□H150	VAC34□□H200						



齿形(ISO标准齿条尺寸)



■带 *号R尺寸适用于19以下齿数。



3/2

型号		带轮形状	轴孔规格dH7(根据胀套孔径表选择)								P.D.	O.D.	F	E	A	W
代码	齿数		H075		H100		H150		H200							
		E形 ST胀套	F形 SH胀套	E形 ST胀套	F形 ST胀套	E形 ST胀套	F形 ST胀套	E形 ST胀套	F形 ST胀套							
VAC01-H075 VAC03-H075 VAC04-H075	14	12-17(无13)				15-17		16-17	16-17	56.6	55.22	61	45	H075 A: 21 W: 26		
	15	14-20				15-20		16-20	16-20	60.64	59.27	67	50			
	16	14-25(无21,23)				15 16 17 18 19 20 22 25		16 17 18 19 20 22 25	16-20	64.68	63.31	70	56			
	17	14-25(无21,23)				15 16 17 18 19 20 22 25		16 17 18 19 20 22 25	16-20	68.72	67.35	80	60			
VAC11-H100 VAC13-H100 VAC14-H100	18	14-25(无21,23)				15 16 17 18 19 20 22 25 28 30 32		16 17 18 19 20 22 25 28 30 32	16-20	72.77	71.39	87	67	H100 A: 27 W: 32		
	19	14-25(无21,23)				15 16 17 18 19 20 22 25 28 30 32		16 17 18 19 20 22 25 28 30 32	16-20	76.81	75.44	87	67			
	20	14-25(无21,23)				15 16 17 18 19 20 22 25 28 30 32		16 17 18 19 20 22 25 28 30 32	16-20	80.85	79.48	87	67			
VAC21-H150 VAC23-H150 VAC24-H150	21	E	14-35 (无26,27 无21,23,31,33)	14-32 (无26,27 无21,23,31,33)	14-35 (无26,27 无21,23,31,33)	14-32 (无26,27 无21,23,31,33)	15 16 17 18 19 20 22 25 28 30 32 35	16 17 18 19 20 22 25 28 30 32 35	16 17 18 19 20 22 25 28 30 32 35	84.89	83.52	95	75	H150 A: 40 W: 45		
	22	F	19-35 (无26,27 无21,23,31,33)	19-32 (无26,27,21, 23,31,33)	19-35 (无26,27,21, 23,31,33)	19-32 (无26,27,21, 23,31,33)	19 20 22 25 28 30 32 35	19 20 22 25 28 30 32 35	19 20 22 25 28 30 32 35	88.94	87.56	104	84			
VAC31-H200 VAC33-H200 VAC34-H200	24		20 22 24	20 22 24	20 22 24	20 22 24	20 22 24 25 28 30 32 35	20 22 24 25 28 30 32 35	20 22 24 25 28 30 32 35	97.02	95.65	111	90	H200 A: 54 W: 59		
	25		25 28 30	25 28 30	25 28 30	25 28 30				101.06	99.69	111	90			
	26		32	32	32 35	32				105.11	103.73	111	90			
	28		32 35	32	32 35	32				113.19	111.82	123	102			
	30		32 35	32	32 35	32				121.28	119.9	127	105			
32		32 35	32	32 35	32	129.36	127.99	135	115							
34		32 35	32	32 35	32	137.45	136.07	144	125							
36		32 35	32	32 35	32	145.53	144.16	152	130							

胀套孔径尺寸

dH7	容许最大扭矩 N.m		D		(L)
	ST胀套	SH胀套	ST胀套	ST胀套	
12	48	23	32	31	10.5
14	73	37	35	36	12
15	78	39	36	37	
16	83	42	37	38	
17	88	45	38	39	13
18	154	48	43	40	
19	163	49	45	42	
20	171	97	46	46	14
22	186	110	48	47	
24	206	121	50	49	
25	216	124	52	51	
28	353	141	54	53	15.5
30	382	149	57	56	
32	412	163	59	58	16.5
35	451	173	63	61	



请按图示订货

VAC01-H075-14-E-d8

型号		带轮形状	轴孔规格d H7	
代码	齿数		H075	H100
VAC01-H075	14	E	E	F
	15	F	8-12	8 10



交期Delivery

7天 发货

○本产品发货时间不含周日