




夹持型高扭矩同步带轮 ◀ S3M/S5M/S8M型




代码	类型	材质		表面处理	附件
		带轮	法兰		
VPM01	夹持型	铝合金	铝合金	本色阳极氧化	内六角圆柱头螺钉


标准齿型



S3M型 (齿距: 3.0)



S5M型 (齿距: 5.0)



S8M型 (齿距: 8.0)

型号		齿数	轴孔规格dH7(最小单位1)	P.D.	O.D.	D	F	E	L	V	带轮公称宽		夹紧螺钉							
代码	齿型										A	W	M-长度	紧固扭矩(N·M)						
VPM01	S3M060 S3M100	24	4	22.92	22.16	13	25	16	9	2	皮带宽度6 S3M060 A:7 W:11	M2-8	0.4							
		26		24.83	24.07		28	18												
		28		26.74	25.98		30	20												
		30		28.65	27.89		32	23												
		32		30.56	29.8		35	25												
		36		34.38	33.62		40	28												
		40		38.2	37.44		44	32												
		44		42.02	41.25		50	38												
		48		45.84	45.07		55	40												
		50		47.75	46.98		60	46												
	60	57.3	56.53	80	60															
	S5M100 S5M150	8 10	24	38.2	37.24	26	45	30	12.5	14	2.5	皮带宽度10 S3M100 A:11 W:15	M3-10	1.5						
			25	39.79	38.83										35	14				
			26	41.38	40.42										40	15.5				
			28	44.56	43.6										45	16.5				
			30	47.75	46.79										50	17.5				
			32	50.93	49.97										55	18.5				
		34	54.11	53.15	60	20														
		36	57.3	56.34	65	21														
		40	63.66	62.7	75	25														
		44	70.03	69.07	85	30														
		48	76.39	75.43	95	35														
		50	79.58	78.62	105	40														
		60	95.49	95.43	135	50														
		S8M150 S8M250	10 12 13 14	20	50.93	49.56	36	58	40	14					2.5	皮带宽度15 S8M150 A:17 W:22	M5-16	6		
				22	56.02	54.65													41	16
				24	61.12	59.74													46	17
				25	63.66	62.29													50	18
			28	71.3	69.93	55	20													
	30		76.39	75.02	60	21														
	32		81.49	80.14	65	22														
	34		86.58	85.21	70	23														
	36		91.67	90.3	75	24														
	40		101.36	100.4	85	28														
	44		106.46	105.5	90	30														
	48		111.56	110.6	95	32														
	50		113.67	112.71	100	34														
	60		123.77	122.81	115	40														
	70		133.87	132.9	135	50														
	80		143.97	143.03	160	60														
90	154.07	153.1	185	70																
100	164.17	163.17	210	80																

同步轮 14



请按图示订货

■VPM01-S8M150-20-d14

型号		轴孔规格dH7(最小单位1)			
代码	齿型	齿数			
VPM01	S8M150	20	12	13	14
	S8M250	22	12	13	14 15 16



交期Delivery

7天

发货

本产品发货时间不含周日