

代码	类型	材质	硬度(肖氏)	颜色	使用温度范围	用途	适用标准
YXC01	P系列	丁腈橡胶	HS65 ⁺¹⁰	黑色	-20-100°C	耐矿物油用	JIS B 2401
YXC02			HS85 ⁺¹⁰		-15-100°C		
YXC11	硅橡胶	HS45 ⁺¹⁰	半透明色	-40-200°C	耐高温用		
YXC12		HS65 ⁺¹⁰	红褐色				
YXC21	氟橡胶	HS65 ⁺¹⁰	黑色	-10-200°C	耐高压用		
YXC22		HS85 ⁺¹⁰		-40-120°C			
YXC31	乙丙橡胶	HS65 ⁺¹⁰	白色	-10-200°C			
YXC41	氟树脂	/	/	白色	-10-200°C		

型号	规格	公称编号	d ₂	d ₁	H	C
YXC41	15	P15	2	+0.15 0	15	1.25
	16	P16			16	
	18	P18			18	
	20	P20			20	
	21	P21			21	
	22	P22			22	
	22A	P22A			22	
	24	P24			24	
	25	P25			25	
	26	P26			26	
	28	P28	28			
	30	P30	30			
	32	P32	32			
	34	P34	34			
	38	P38	38			
	40	P40	40			
	42	P42	42			
	48	P48	48			
	50	P50	50			
				3	+0.20 0	19
			20			
			22			
			24			
			25			
			26			
			28			
			30			
			31			
			32			

■ YXC01-YXC31的详细参数表见下页

请按图示订货

YXC01-3


型号

代码	规格
YXC01	3

交期Delivery

3天 发货

○本产品发货时间不含周日



型号	规格	公称编号	d ₂	d ₁				配合尺寸		
				尺寸	YXC01 YXC02	YXC11 YXC12 YXC31	YXC21 YXC22	d ₁	H	
YXC01 YXC02 YXC11 YXC12 YXC21 YXC22 YXC31	3	P3	1.9±0.07	2.8	±0.13	±0.20	±0.15	3	0	+0.04 0
	4	P4		3.8						
	5	P5		4.8						
	6	P6		5.8						
	7	P7		6.8						
	8	P8		7.8						
	9	P9		8.8						
	10	P10		9.8						
	10A	P10A		9.8						
	11	P11		10.8						
11.2	P11.2	11.0								
12	P12	11.8								
12.5	P12.5	12.3								
14	P14	13.8								
15	P15	14.8								
16	P16	15.8								
18	P18	17.8								
20	P20	19.8								
21	P21	20.8								
22	P22	21.8	±0.17	±0.26	±0.20	11	0	+0.07 0		
22A	P22A	21.7								
22.4	P22.4	22.1								
24	P24	23.7								
25	P25	24.7								
25.5	P25.5	25.2								
26	P26	25.7								
28	P28	27.7								
29	P29	28.7								
29.5	P29.5	29.2								
30	P30	29.7	±0.18	±0.27	±0.21	12	0	+0.09 0		
31	P31	30.7								
31.5	P31.5	31.2								
32	P32	31.7								
34	P34	33.7								
35	P35	34.7								
35.5	P35.5	35.2								
36	P36	35.7								
38	P38	37.7								
39	P39	38.7								
40	P40	39.7	±0.19	±0.29	±0.23	14	0	+0.07 0		
41	P41	40.7								
42	P42	41.7								
44	P44	43.7								
45	P45	44.7								
46	P46	45.7								
48	P48	47.7								
50	P50	49.7								
50A	P50A	49.7								
52	P52	51.6								
53	P53	52.6								
55	P55	54.6	±0.20	±0.30	±0.24	15	0	+0.07 0		
56	P56	55.6								
58	P58	57.6								
60	P60	59.6								
62	P62	61.6								
63	P63	62.6								
65	P65	64.6								
67	P67	66.6								
70	P70	69.6								
71	P71	70.6								
75	P75	74.6	±0.21	±0.32	±0.25	16	0	+0.07 0		
80	P80	79.6								