


精密型 橡皮管用快拧接头 ◀ 直接头/弯接头 外螺纹

气动接头
39




代码	类型	材质
DCY01	外螺纹 直接头	SUS316
DCY21	外螺纹 弯接头	SUS316

直接头/外螺纹
DCY01



弯接头/外螺纹
DCY21



■ 直接头/外螺纹

型号	公称	适用软管	R	A	B	E ₁	H	C	S ₁	V	喷嘴	有效断面积	重量
代码	管外径D	型号	内径								孔径	(mm ²)	(g)
DCY01	4	1	2	R1/8	8	25.5	21.5	5.5	10	10	1.3	0.8	13
		2		R1/4	11	28.5	22.5			14			
	6	1	4	R1/8	8	25.5	21.5	6	12	12	3	6	16
		2		R1/4	11	28.5	22.5			14			21
		3		R3/8	12	29.5	23.2			17			30
	8	1	6	R1/8	8	27.5	23.5	7	14	14	5	17	22
		2		R1/4	11	30.5	24.5						25
		3		R3/8	12	31.5	25.2						34
	10	2	8	R1/4	11	33.5	27.5	9	17	17	6.5	26	38
		3		R3/8	12	34.5	28.2						43
		4		R1/2	15	37.5	29.3			21			60
	12	2	10	R1/4	11	33.5	27.5	9	19	19	8.5	45	44
		3		R3/8	12	34.5	28.2						50
		4		R1/2	15	37.5	29.3			21			63

■ 弯接头/外螺纹

型号	公称	适用软管	R	A	B	L ₁	I	E ₁	E ₂	E ₃	F	S ₁	S ₂	喷嘴	有效断面积	重量
代码	管外径D	型号	内径											孔径	(mm ²)	(g)
DCY21	4	1	2	R1/8	8	27.9	23.9	21	27.9	21	5.5	10	12	1.4	0.7	27
		2		R1/4	11	30.1	24.1	22	30.1	22			14			
	6	1	4	R1/8	8	27.9	23.9	21	27.9	21	6	12	12	3	5.5	28
		2		R1/4	11	30.1	24.1	22	30.1	22			14			37
		3		R3/8	12	40	33.6	29	40	29			19			87
	8	1	6	R1/8	8	30.8		25	34.8	25	13.5	14	17	5	14.5	62
		2		R1/4	11	34.8										59
		3		R3/8	12	33.6										87
	10	2	8	R1/4	11	40	34	29	40	29	16.5	17	19	6	23	88
		3		R3/8	12	33.6										89
		4		R1/2	15	44.3	36.1	31	44.3	31			23			127
	12	2	10	R1/4	11	40	34	29	40	29	9	19	19	7.5	38	88
		3		R3/8	12	33.6										90
		4		R1/2	15	44.3	36.1	31	44.3	31			23			131



请按图示订货

■ DCY01-D6-1

型号	公称	适用软管
代码	型号	内径
DCY01	D 6	1 4



交期Delivery

9天

发货

○ 本产品发货时间不含周日



www.vipdo.cn 400-098-1117

工厂自动化零件一站式采购平台

汇集国内外知名品牌，让采购更便捷，让设计更高效！