




双排链轮 ◀ 40B(08A)/50B(10A)系列



代码	类型	材质	热处理	表面处理	附件
KQZ40B	40系列	S45C	齿顶高频	发黑	固定螺丝
KQZ50B	50系列				



- 工艺问题，无法保证多数产品齿顶一致重合；
- 日标链轮请勿与国标链条配合；
- 齿顶和键槽的偏置为±0.5mm。

■ 轴孔加工尺寸表

轴孔直径 D	键槽 b2×t2	固定螺丝 M
15	5×2.3	6
18~20	6×2.8	
25~30	8×3.3	
35	10×3.3	8
40	12×3.3	

型号		轴孔直径D _{H7}					D _p	D _o	盖 毅			Z	重量 (g)	
代码	齿数								H	L	W			
KQZ40B	12	15	18				49.07	55	34	35	7.2	27.8	0.33	
	13	18	20				53.07	59	38				0.4	
	14	18	20				57.07	63	42				0.49	
	15	20	25				61.08	67	46				0.57	
	16	20	25				65.1	71	50				0.66	
	17	25	28	30			69.12	76	54				0.76	
	18	25	28	30	35		73.14	80	59				0.89	
	19	25	28	30	35		77.16	84	63				1	
	20	25	28	30	35		81.18	88	67				1.14	
21	25	28	30	35		85.21	92	71				1.23		
KQZ50B	12	18	20				61.34	69	43	40	8.7	31.3	0.63	
	13	20	25	28			66.34	74	48				0.75	
	14	20	25	28	30		71.34	79	53				0.9	
	15	20	25	28	30	35		76.35	84				58	1.04
	16	25	28	30	35	40		81.37	89				63	1.22
	17	25	28	30	35	40		86.39	94				68	1.41
	18	25	28	30	35	40		91.42	100				73	1.61
	19	25	28	30	35	40		96.45	105				79	1.8
	20	25	28	30	35	40		101.48	110				84	1.95
21	25	28	30	35		106.51	115	89				2.27		



请按图示订货

■ KQZ40B-13-D20

型式	齿数	轴孔直径 DH7
KQZ40B	12	15 18
	13	18 20



交期 Delivery

7 天

发货

○ 本产品发货时间不含周日

